


# CHIP LED - 0805 - WHITE

## - CC - WNB0805DS - DD -

### FEATURES


- Viewing angle: 140 deg
- The materials of the LED dice is InGaN
- 2.0mm x 1.25mm x 0.70mm
- RoHS compliant led-free soldering compatible



**ATTENTION**

OBSERVE PRECAUTIONS  
FOR HANDLING  
ELECTROSTATIC SENSITIVE DEVICES

### PACKAGE OUTLINE



All dimensions are in millimeters (inches); Tolerances are ±0.1mm (0.004inch) unless otherwise noted.


### ABSOLUTE MAXIMUM RATINGS AT Ta - 25°C

PARAMETER	SYMBOL	VALUE	UNIT
Forward Current	If	20	mA
Reverse Voltage	Vr	5	V
Operating Temperature Range	Top	-20 ~ +85	°C
Storage Temperature Range	Tstg	-35 ~ +85	°C
Pulse Forward Current	Ifp	100	mA
Electrostatic Discharge	ESD	1000(HBM)	V

### ELECTRO-OPTICAL CHARACTERISTICS AT Ta - 25°C

PARAMETER	TEST CONDITION	SYMBOL	VALUE			UNIT
			MIN	TYPE	MAX	
Forward Voltage	If - 20mA	Vf	2.6	-	2.7	V
			2.7	-	2.8	V
			2.8	-	2.9	V
			2.9	-	3.0	V
			3.0	-	3.1	V
			3.1	-	3.2	V
			3.2	-	3.3	V
			3.3	-	3.4	V
			3.4	-	3.5	V
Luminous Intensity	If - 20mA	Iv	350	-	400	mcd
			400	-	450	mcd
			450	-	500	mcd
			500	-	550	mcd
			550	-	600	mcd
			600	-	650	mcd
			650	-	700	mcd
			700	-	750	mcd
			750	-	800	mcd
			800	-	850	mcd
			850	-	930	mcd
930	-	1020	mcd			
Viewing Angle at 50% Iv	If - 20mA	2θ 1/2	-	140	-	Deg
Reverse Current	Vr - 5V	Ir	-	-	10	µA








**CHROMATICITY BIN**



BIN CODE	CIE-X1	CIE-Y1	CIE-X2	CIE-Y2	CIE-X3	CIE-Y3	CIE-X4	CIE-Y4
B01	0.2700	0.2705	0.2663	0.2746	0.2764	0.2923	0.2794	0.2872
B02	0.2741	0.2660	0.2700	0.2705	0.2794	0.2872	0.2826	0.2819
B03	0.2779	0.2618	0.2741	0.2660	0.2826	0.2819	0.2856	0.2767
B04	0.2794	0.2872	0.2764	0.2923	0.2874	0.3114	0.2898	0.3056
B05	0.2826	0.2819	0.2794	0.2872	0.2898	0.3056	0.2923	0.2999
B06	0.2856	0.2767	0.2826	0.2819	0.2923	0.2999	0.2947	0.2942
K01	0.2898	0.3056	0.2874	0.3114	0.3013	0.3309	0.3029	0.3240
K02	0.2923	0.2999	0.2898	0.3056	0.3029	0.3240	0.3045	0.3170
K03	0.2947	0.2942	0.2923	0.2999	0.3045	0.3170	0.3061	0.3101
K04	0.3029	0.3240	0.3013	0.3309	0.3148	0.3498	0.3156	0.3418
K05	0.3045	0.3170	0.3029	0.3240	0.3156	0.3418	0.3164	0.3338
K06	0.3061	0.3101	0.3045	0.3170	0.3164	0.3338	0.3173	0.3258



# TYPICAL OPTICAL CHARACTERISTICS CURVES



# REFLOW PROFILE


## - Soldering Condition

Recommended Soldering  
After reflow soldering rapid cooling should be avoided


REFLOW SOLDERING		HAND SOLDERING	
Pre-Heat	160 °C ~ 180°C	Temperature	300°C
Pre-Heat Time	120 Seconds Max.	Soldering Time	3 Second Max - One Time Only
Peak Temperature	260°C Max		
Soldering Time	10 Seconds Max		
Condition	Refer to Temperature-profile		

## - Temperature - profile (surface of circuit board)

Use the following conditions shown in figure



## - Recommend Pad Design (Units: mm)




Reflow soldering should not be done more than two times  
When soldering, do not put stress on the LEDs during heating

## - Soldering Iron

When hand soldering, keep the temperature of the iron under 300°C, and at that temperature keep the time under 3 sec.  
The hand soldering should be done only a time  
The basic spec is ≤5 sec. when the temperature of 260°C, do not contact the resin when hand soldering.

## - Rework

Customer must finish rework within 5 sec under 260°C  
The head of iron can not touch the resin  
Twin-head type is preferred



## RELIABILITY

### - TEST ITEMS AND RESULTS

TYPE	TEST ITEM	REF STANDARD	TEST CONDITIONS	NOTE	NUMBER OF DAMAGED
Environmental Sequence	Resistance to Soldering Heat (Reflow Soldering)	JESD22 - B106	Tsld - 260°C, 10 sec	2 times	0/22
	Temperature Cycle	JESD22 - A104	-40°C 30 min 25°C ↑↓ 5min 100°C 30 min	300 cycle	0/22
	Thermal Shock	JESD22 - A106	-35°C 15min ↑↓ 85°C 15 min	300 cycle	0/22
	High Temperature Storage	JESD22 - A103	T <sub>a</sub> - 100°C	1000 hrs	0/22
	Low Temperature Storage	JESD22 - A119	T <sub>a</sub> - 40°C	1000 hrs	0/22
Operation Sequence	Life Test	JESD22 - A108	T <sub>a</sub> - 25°C I <sub>F</sub> - 20mA	1000 hrs	0/22

### - CRITERIA FOR JUDGING THE DAMAGE

ITEM	SYMBOL	TEST CONDITIONS	CRITERIA FOR JUDGEMENT	
			MIN.	MAX.
Forward Voltage	VF	IF - 20mA	-	U.S.L *) x 1.1
Reverse Current	IR	VR - 5V	-	U.S.L*) x 2.0
Luminous Intensity	IV	IF - 20mA	L.S.L**) x 0.5	-


- U.S.L.: Upper Standard Level  
- L.S.L.: Lower Standard Level

NOTE: Any reliability test standard change is confidential

## PACKAGING SPECIFICATIONS

### - Feeding Direction


### - Dimensions of Reel (Unit: mm)




A	8.0 ± 0.1mm
B	178 ± 1mm
C	60 ± 1mm
D	13.0 ± 0.5mm

## PACKAGING SPECIFICATIONS

- Dimensions of Tape (Unit: mm)




- Arrangement of Tape




**NOTE:** Empty component pockets are sealed with top cover tape  
 The maximum number of missing lamps is two:  
 The cathode is oriented towards the tape sprocket hole in accordance with ANSI/EIA RS-481 specifications.  
 4,000 pcs / Reel

## PACKAGING SPECIFICATIONS



- Label



- Cautions

- Packaging Specification

- Reeled products (numbers of products are 4,000 pcs) packed in a seal off moisture-proof bag along with a desiccant one by one, Eighty moisture-proof bag of maximums are put the outside box (size: about 545mm x about 375mm x about 275mm) Together with buffer material, and it is packed. (Pare No., Lot No., quantity should appear on the label on the moisture-proof bag, part No. And quantity should appear on the label on the cardboard box. ) The number of the loading steps of outside box (cardboard box) has two steps.

- Storage Conditions

- **Before Opening the Packaging** - The LEDs should be kept at 30°C or less and 70% RH or less. The LEDs should be used within a year. When storing the LEDs, moisture proof packaging with absorbant material is recommended.

- **After Opening the Package** - The LEDs should be kept at 30°C or less and 50% RH or less. The LEDs should be soldered withing 168 hours (7 days) after opening the package. If unused LEDs remain, they should be stored in moisture proof packages, such as sealed containers with packages of moisture absorbant material. It is also recommended to return the LEDs to the original moisture proof bag and to reseal the moisture proof bag again.

